


Datasheet for: 106645


3/2-way mini solenoid valve directly controlled, NC, 12 VDC

3/2-way mini solenoid valve directly controlled, DN 1.5 mm, NC, 12 VDC, for equipment plug, Pressure 0-7 bar, Temp. -5 °C to 45 °C. Directly controlled 3/2-way solenoid valves specially designed for pneumatic applications. These valves are provided with a flange for assembly on an individual base or multiple manifold base. They feature a monostable manual operator. The scope of supply includes two fixing bolts and a flange gasket. The coils can be turned 180°.

Type number	MV 1052.3
Article number	106645
EAN/barcode	 4047322156530
Your price	24,46 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Coil power	2.5 W
Connection	For plug connector
Function	NC
Height	42.0 mm
Material	Plastic
Max. operating pressure	7 bar
Max. temperature range	45 °C
Medium	Filtered, unlubricated compressed air
Min. temperature range	-5 °C
Nominal Ø	1.5 mm
Opening and closing times	10 to 12 ms (depending on pressure)
Page No.	HK481
Plate on manual operator	Silver
Sealant	NBR, stainless steel
Voltage	12 V DC
Width	15.0 mm

Variants

<i>Article number</i>	<i>Function</i>	<i>Voltage</i>	<i>Connection</i>	<i>Max. operating pressure</i>	<i>Price</i>
106645	NC	12 V DC	For plug connector	7 bar	24,46 € / Stk
106642	NC	24 V DC	Cable (30 cm)	7 bar	25,98 € / Stk
106643	NC	24 V DC	For plug connector	7 bar	24,46 € / Stk
106644	NC	12 V DC	Cable (30 cm)	7 bar	25,98 € / Stk
106646	NO	24 V DC	Cable (30 cm)	5 bar	25,98 € / Stk
106647	NO	24 V DC	For plug connector	5 bar	24,46 € / Stk
106648	NO	12 V DC	Cable (30 cm)	5 bar	25,98 € / Stk
106649	NO	12 V DC	For plug connector	5 bar	24,46 € / Stk