

## Datasheet for: 107049


**Compact pressure regulator, Push-in connector for hose 8, G 1/4**

Compact pressure regulator, Push-in connector for hose 8, G 1/4, Control range - 8 bar, Temp. °C to 70 °C, nickel-plated brass . Piston pressure regulator with self-relieving design, hollow bolt and pivoting ring piece. The regulator is connected directly into the consumer (e.g. cylinder, handling equipment, etc.). The working pressure can thus be adapted to the specific application.

Type number	3621.014-8
-------------	------------

Article number	107049
----------------	--------

EAN/barcode	 4047322181686
-------------	--

Your price	27,60 € / Stk
------------	---------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Adjusting screw	Nickel-plated brass
B	63.0 mm
C	24.0 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	8 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. control range	8.0 bar
Max. input pressure	10 bar
Max. temperature range	70 °C
Min. control range	0.0 bar
Page No.	HK506
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/4
a/f	17 mm

## Variants

Article number	Thread	For hose	a/f	Price
107049	G 1/4	8 mm	17 mm	27,60 € / Stk
107045	G 1/8	4 mm	15 mm	27,60 € / Stk
107046	G 1/8	6 mm	15 mm	27,60 € / Stk
107047	G 1/8	8 mm	15 mm	27,60 € / Stk
107048	G 1/4	6 mm	17 mm	27,60 € / Stk
107050	G 1/4	10 mm	17 mm	27,60 € / Stk

## More Pictures

