


Datasheet for: 107270


Distributor 3 quick-connect couplings I.D. 7.2, Plug nipple G 3/8

Distributor with 3 quick-connect couplings I.D. 7.2, Bright brass, with plug nipple I.D. 7.2 - 7.8, G 3/8, Operating pre. 0-35 bar . 1, 2 or 3-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Type number	245.59
Article number	107270
EAN/barcode	 4047322368155
Your price	24,48 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Comprising distributor	Brass with a bare metal surface, G 3/8 IT
Connection	Plug DN 7.2 to 7.8 / G 3/8
Couplings	DN 7.2, brass with a bare metal surface, G 3/8 ET
Height	117.0 mm
Housing	Brass with a bare metal surface
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure	35 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK535
Page No. SK	SK020
Sealant	Industrial adhesives, medium strength
Securing	Industrial adhesives, medium strength
Width	115.0 mm

Variants

Article number	Connection	Comprising distributor	Couplings
107270	Plug DN 7.2 to 7.8 / G 3/8	Brass with a bare metal surface, G 3/8 IT DN 7.2, brass with a bare metal surface,	
107271	Plug DN 7.2 to 7.8 / G 1/2	Brass with a bare metal surface, G 1/2 IT DN 7.2, brass with a bare metal surface,	

More Pictures

