

Datasheet for: 135067


Straight push-in fitting G 3/8 o., for hose exterior Ø 8 mm

Straight push-in fitting, Exterior hexagonal, G 3/8 o. for hose exterior Ø 8 mm, Working pressure max. 20 bar, Stainless steel 1.4404. For use in more aggressive environments and corrosive media.

Type number	844.038-8 ES
-------------	--------------

Article number	135067
----------------	--------

EAN/barcode



4047322492744

Your price	27,72 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
------------	---

Quantity Unit	Stk
---------------	-----

Packaging Unit	1
----------------	---

Content	1 Stk
---------	-------

Minimum order quantity	1
------------------------	---

Productdata

For tube O.D.	8 mm
L1	23.8 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	20 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	HK718
Standard thread	DIN EN ISO 228-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	G 3/8
Working pressure pulsate	10.0 bar
a/f	21 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
135067	G 3/8	8 mm	21 mm	27,72 € / Stk
135068	G 3/8	10 mm	21 mm	35,28 € / Stk
135064	G 1/4	8 mm	17 mm	21,91 € / Stk
135062	G 1/4	4 mm	17 mm	19,03 € / Stk
135065	G 1/4	10 mm	17 mm	24,04 € / Stk
135074	G 1/2	16 mm	27 mm	62,22 € / Stk
135063	G 1/4	6 mm	17 mm	18,26 € / Stk
135069	G 3/8	12 mm	21 mm	44,71 € / Stk
135060	G 1/8	6 mm	14 mm	16,89 € / Stk
135072	G 1/2	12 mm	27 mm	50,67 € / Stk
135071	G 1/2	10 mm	27 mm	43,97 € / Stk
135061	G 1/8	8 mm	14 mm	18,93 € / Stk
135073	G 1/2	14 mm	27 mm	55,89 € / Stk
135058	M5	4 mm	11 mm	16,23 € / Stk
135059	G 1/8	4 mm	14 mm	16,44 € / Stk
135066	G 1/4	12 mm	19 mm	39,45 € / Stk
135070	G 3/8	14 mm	22 mm	53,28 € / Stk

More Pictures

