


Datasheet for: 101506


Mini pressure regulator, G 1/4 ET/ET, pre-set 2 bar

Mini pressure regulator, G 1/4 ET / ET, Working pressure (pre-set) 2 bar, PN max. 12 bar . This preset pressure regulator guarantees optimal pressure conditions, especially in blow guns. The pressure regulator is inserted into the compressed air line. Fits onto any 1/4" thread and maintains the pressure at optimum, thus helping to reduce the costs for energy. Tamper-proof.

Type number	638.42
Article number	101506
EAN/barcode	 4047322247375
Your price	24,81 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Flow rate	- 400 l/min
Housing	Brass
L	24.0 mm
Max. input pressure	12 bar
Max. temperature range	60 °C
Min. temperature range	-20 °C
Page No.	HK965
Page No. SF	SF033
Spring	Stainless steel
Thread	G 1/4 ET/ET
Working pressure (preset)	2.0 bar

Variants

<i>Article number</i>	<i>Working pressure (preset)</i>	<i>Price</i>
101506	2.0 bar	24,81 € / Stk
101508	6.0 bar	24,81 € / Stk
101507	4.0 bar	24,81 € / Stk

More Pictures

