


## Datasheet for: 101508


**Mini pressure regulator, G 1/4 ET/ET, pre-set 6 bar**

Mini pressure regulator, G 1/4 ET / ET, Working pressure (pre-set) 6 bar, PN max. 12 bar . This preset pressure regulator guarantees optimal pressure conditions, especially in blow guns. The pressure regulator is inserted into the compressed air line. Fits onto any 1/4" thread and maintains the pressure at optimum, thus helping to reduce the costs for energy. Tamper-proof.

Type number	638.46
Article number	101508
EAN/barcode	 4047322327695
Your price	24,81 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Flow rate	- 400 l/min
Housing	Brass
L	24.0 mm
Max. input pressure	12 bar
Max. temperature range	60 °C
Min. temperature range	-20 °C
Page No.	HK965
Page No. SF	SF033
Spring	Stainless steel
Thread	G 1/4 ET/ET
Working pressure (preset)	6.0 bar

## Variants

Article number	Working pressure (preset)	Price
101508	6.0 bar	24,81 € / Stk
101507	4.0 bar	24,81 € / Stk
101506	2.0 bar	24,81 € / Stk

## More Pictures

