

Datasheet for: 135287



Straight push-in connector with plug nipple 10 mm, reducing

Straight push-in connector with plug nipple 10 mm, reducing, for hose exterior Ø 8 mm, Working pressure max 20 bar Stainless steel . For use in more aggressive environments and corrosive media.

Type number	859.1008 ES
-------------	-------------

Article number	135287
----------------	--------

EAN/barcode



4047322494939

Your price	24,83 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	8 mm
L1	42.8 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	20 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	HK724
Plug connection	10 mm
Suitable pipe materials	PVDF, PTFE, PA, PU
Working pressure pulsate	10.0 bar

Variants

<i>Article number</i>	<i>For tube O.D.</i>	<i>Price</i>
135287	8 mm	24,83 € / Stk
135286	6 mm	27,44 € / Stk
135288	8 mm	30,33 € / Stk
135289	10 mm	31,47 € / Stk
135283	4 mm	19,05 € / Stk
135284	4 mm	24,26 € / Stk
135290	12 mm	45,91 € / Stk
135291	12 mm	49,38 € / Stk
135285	6 mm	22,81 € / Stk

More Pictures

