


Datasheet for: 102158


Glycerine pressure gauge, rear centric, G 1/4, - 600 bar, Ø 63

Glycerine pressure gauge, CrNi steel housing, Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range 0-600 bar, Ø 63 . Glycerine-filled bourdon-tube pressure gauge. For measurements in areas with high, dynamic pressure loads and vibration levels. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Type number	816-C
Article number	102158
EAN/barcode	 4047322120586
Your price	27,73 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	1.6
Connection	G 1/4
Connection position	rear, central
Crimped bezel	CrNi steel, with glossy metal surface (3-hole bezel)
Diameter	63 mm
Front glass	Transparent plastic
Housing	CrNi steel, with bare metal surface
Lower / Upper range limit	Positive pressure
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Measuring element	CrNi steel
Measuring range max. bar	600.0
Measuring range min. bar	0.0
Min. ambient temperature	-20 °C
Movement	Copper alloy
Page No.	HK208
Scale graduation in the bar area	20.0 bar

Type

213.53

Variants

<i>Article number</i>	<i>Measuring range min. bar</i>	<i>Measuring range max. bar</i>	<i>Price</i>
102158	0.0	600.0	27,73 € / Stk
102143	-1.0	0.0	27,73 € / Stk
102144	0.0	1.0	27,73 € / Stk
102145	0.0	1.6	27,73 € / Stk
102146	0.0	2.5	27,73 € / Stk
102147	0.0	4.0	27,73 € / Stk
102148	0.0	6.0	27,73 € / Stk
102149	0.0	10.0	27,73 € / Stk
102150	0.0	16.0	27,73 € / Stk
102151	0.0	25.0	27,73 € / Stk
102152	0.0	40.0	27,73 € / Stk
102153	0.0	60.0	27,73 € / Stk
102154	0.0	100.0	27,73 € / Stk
102155	0.0	160.0	27,73 € / Stk
102156	0.0	250.0	27,73 € / Stk
102157	0.0	400.0	27,73 € / Stk
102159	0.0	1000.0	27,73 € / Stk