

Datasheet for: 110276


Straight screw-in fitting PP, G 1 o., for hose exterior Ø 32 mm

Straight screw-in fitting PP, G 1 o., for hose exterior Ø 32 mm, Working pressure max. 16 bar . Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. All our push-in fittings made of POM have the following approvals: drinking water DVGW, KTW, FDA and NSF. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Type number	65.100-32
Article number	110276
EAN/barcode	 4047322337724
Your price	18,40 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	32 mm
L1	111.4 mm
Material	Polypropylene, glass fibre-reinforced (PP)
Max. operating temperature	20 °C
Max. working pressure	16 bar
Page No.	HK939
Thread	G 1
a/f	46 mm

Variants

<i>Article number</i>	<i>Thread</i>	<i>a/f</i>	<i>Max. working pressure</i>	<i>Price</i>
110276	G 1	46 mm	16 bar	18,40 € / Stk
110277	G 1 1/2	49 mm	12 bar	19,33 € / Stk

More Pictures

