

## Datasheet for: 108377

**Inline ejector »SLP«, Nozzle size 0.7 mm**

Inline ejector »SLP«, Nozzle size 0.7 mm, Compressed air connection 4 mm, Vacuum connection 4 mm, PN max. 4.5 bar, Plastic. For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet. Properties



•Vacuum generator with a high maximum vacuum value (85%)

•No moving parts, which means no wear and no maintenance

•Extremely space-saving installation, ideal where space is restricted

•Minimum compressed air consumption

•Low noise output

Applications

•Direct installation on the suction pad by screwing / plugging into the distribution beam

•Handling all kinds of workpiece

Type number	SLP 07
Article number	108377
EAN/barcode	 4047322198998
Your price	27,99 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Air consumpt. during evac.	25 l/min
Compressed air inlet Connection	4 mm Plug connection
Degree of evacuation	85 %

Exhaust air outlet	-
Housing	Plastic
Length	57.0 mm
Max. operating pressure	4.5 bar
Max. suction rate	16 l/min
Nozzle size	0.7 mm
Nozzle system	Aluminium
Page No.	WEB
Vacuum inlet	4 mm
Weight	5.0 g

## Variants

<i>Article number</i>	<i>Nozzle size</i>	<i>Max. suction rate</i>	<i>Air consumpt. during evac.</i>	<i>Price</i>
108377	0.7 mm	16 l/min	25 l/min	27,99 € / Stk
108376	0.5 mm	8 l/min	13 l/min	26,12 € / Stk