


Datasheet for: 101300


Welding technology pressure gauge, acetylene, G 1/4, - 40 bar

Welding technology pressure gauge, acetylene, Connection radial bottom, G 1/4, Goods class 2.5, Measurement range 0-40 bar, Ø 63 . Bourdon-tube pressure gauge acc. to EN 562. For welding systems and cutting machines or similar processes.

Type number	413
Article number	101300
EAN/barcode	 4047322085274
Your price	18,53 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	2.5
Connection	G 1/4
Connection position	radial on bottom
Description	Content pressure gauge (acetylene)
Diameter	63 mm
Front glass	Polycarbonate
Housing	Steel, brass-coloured, pressure relief in the rear wall
Marking	acetylene
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Measuring element	Copper alloy
Measuring range max. bar	40.0
Measuring range min. bar	0.0
Min. ambient temperature	-40 °C
Movement	Copper alloy
Page No.	HK205
Scale graduation in the bar area	2.0 bar
Type	111.11

Variants

<i>Article number</i>	<i>Measuring range max. bar</i>	<i>Marking</i>	<i>Price</i>
101300	40.0	acetylene	18,53 € / Stk
101297	16.0	oxygen	18,40 € / Stk
101298	315.0	oxygen	18,53 € / Stk
101299	2.5	acetylene	18,53 € / Stk