


Datasheet for: 107879


Safety jaw coupling with interior thread, G 3/8, DN 13

Safety jaw coupling with interior thread, G 3/8, DN 13, Malleable cast iron, Operating pressure max. 16 bar, Temp. -40°C to 95°C. Universal standard coupling in safety design according to DIN 3238 for absolutely secure compressed air lines on construction sites or in industry. Easy to couple, secured against accidental opening: just screw the ring tight after coupling! - Robust couplings with malleable iron head, steel stem with special profile, zinc plated and yellow chromated - Chrome VI-free, with double safety lock - Large bore for increased flow rate

| | |
|----------------|--|
| Type number | KI 38 S |
| Article number | 107879 |
| EAN/barcode |  4047322260084 |
| Your price | 18,53 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|----------------|
| Claw distance | 42 mm |
| DN | 13.0 |
| H | 63.0 mm |
| L | 61.7 mm |
| Material | Malleable iron |
| Max. operating pressure | 16 bar |
| Max. operating temperature | 95 °C |
| Min. operating temperature | -40 °C |
| Page No. | HK613 |
| Page No. SF | SF078 |
| Sealant | NBR |
| Thread | G 3/8 |
| a/f | 24 mm |

Variants

| <i>Article number</i> | <i>DN</i> | <i>Thread</i> | <i>a/f</i> | <i>Price</i> |
|-----------------------|-----------|---------------|------------|---------------|
| 107879 | 13.0 | G 3/8 | 24 mm | 18,53 € / Stk |
| 107881 | 17.0 | G 3/4 | 32 mm | 21,56 € / Stk |
| 107882 | 17.0 | G 1 | 41 mm | 22,71 € / Stk |
| 107880 | 17.0 | G 1/2 | 24 mm | 18,53 € / Stk |