


Datasheet for: 107880


Safety jaw coupling with interior thread, G 1/2, DN 17

Safety jaw coupling with interior thread, G 1/2, DN 17, Malleable cast iron, Operating pressure max. 16 bar, Temp. -40°C to 95°C. Universal standard coupling in safety design according to DIN 3238 for absolutely secure compressed air lines on construction sites or in industry. Easy to couple, secured against accidental opening: just screw the ring tight after coupling! - Robust couplings with malleable iron head, steel stem with special profile, zinc plated and yellow chromated - Chrome VI-free, with double safety lock - Large bore for increased flow rate

Type number	KI 12 S
Article number	107880
EAN/barcode	 4047322260091
Your price	18,53 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Claw distance	42 mm
DN	17.0
H	63.0 mm
L	60.7 mm
Material	Malleable iron
Max. operating pressure	16 bar
Max. operating temperature	95 °C
Min. operating temperature	-40 °C
Page No.	HK613
Page No. SF	SF078
Sealant	NBR
Thread	G 1/2
a/f	24 mm

Variants

<i>Article number</i>	<i>DN</i>	<i>Thread</i>	<i>a/f</i>	<i>Price</i>
107880	17.0	G 1/2	24 mm	18,53 € / Stk
107881	17.0	G 3/4	32 mm	21,56 € / Stk
107879	13.0	G 3/8	24 mm	18,53 € / Stk
107882	17.0	G 1	41 mm	22,71 € / Stk