

## Datasheet for: 107955



**Tempered coupling DN 9, Taps 13 mm, Blocking valve, Sleeve 90°**

Tempered coupling DN 9, Taps 13 mm, Blocking valve, Brass, Hose sleeve 90°, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	280.03
-------------	--------

Article number	107955
----------------	--------

EAN/barcode	
-------------	--



4047322258692

Your price	18,53 € / Stk
------------	---------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Ball	Stainless steel
Hose connection	13 mm
Hose stem type	90°
Length	50.5 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK617
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel

## Variants

<i>Article number</i>	<i>Hose stem type</i>	<i>Price</i>
107955	90°	18,53 € / Stk
107953	straight	13,16 € / Stk
107954	45°	18,53 € / Stk