

Datasheet for: 107958


Tempered coupling DN 9, Taps 13 mm, Brass, Hose sleeve 90°

Tempered coupling DN 9, Taps 13 mm, Brass, Hose sleeve 90°, Operating pressure max. 15 bar, Medium/ambient temp. -20 °C to 160 °C . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	280.13
-------------	--------

Article number	107958
----------------	--------

EAN/barcode	 4047322258746
-------------	--

Your price	18,53 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Hose connection	13 mm
Hose stem type	90°
Length	50.5 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK617
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel

Variants

<i>Article number</i>	<i>Hose stem type</i>	<i>Price</i>
107958	90°	18,53 € / Stk
107956	straight	10,66 € / Stk
107957	45°	18,53 € / Stk