

Datasheet for: 106819


Pneumatically releasable check valve »lineonline« for hose Ø 6 mm

Pneumatically releasable check valve »lineonline«, Hose - hose, for hose Ø 6 mm, Operating pressure max. 10 bar . For stopping and positioning the cylinder. If a signal is present at the pilot port, air can flow to and from the cylinder. If no pilot signal is present, the cylinder exhaust port is shut off by the stop valve. The cylinder is stopped.

Type number	493-06
Article number	106819
EAN/barcode	 4047322390101
Your price	25,07 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	49.4 mm
B	43.2 mm
Body	Technopolymer
Control air port	4 mm
Flow rate at 6.3 bar and Δp 1.0 bar	400 NI/min
For pipe Ø	6.0 mm
l	14.6 mm
Internal parts	Nickel-plated brass, brass, technopolymer, stainless steel
Max. operating pressure	10 bar
Max. temperature range	60 °C
Min. temperature range	-20 °C
Page No.	HK494
Pneumatic symbols	On housing
Sealant	NBR

Variants

Article number	For pipe Ø	Flow rate at 6.3 bar and Δp 1.0 bar	Price
106819	6.0 mm	400 NI/min	25,07 € / Stk
106820	8.0 mm	790 NI/min	25,52 € / Stk

More Pictures

