


Datasheet for: 103171


Ball valve standard design, red steel lever, IT/IT, G 1

Ball valve standard design, red steel lever, IT/IT, nickel-plated brass, Operating temp. -15 °C to 90 °C, G 1, PN max. 40 bar .
 Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture.

Type number	330.06-R
Article number	103171
EAN/barcode	 4047322277716
Your price	25,17 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	105.0 mm
B	52.3 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	25.0
E	12.0 mm
F	12.0 mm
Hand lever	Steel, with plastic coating
L	69.0 mm
Material	Nickel-plated brass
Max. operating temperature	90 °C
Min. operating temperature	-15 °C
PN	40 bar
Page No.	HK270
Page No. TS	TS005
Standard thread	G thread acc. to DIN EN ISO 228-1
Stem seal	2 O-rings HNBR/EPDM peroxide crosslinked, sealing ring PTFE
Thread	G 1
Thread material	Brass with a bare metal surface

Variants

Article number	Thread	DN	Price
103171	G 1	25.0	25,17 € / Stk
103167	G 1/4	8.0	11,76 € / Stk
103172	G 1 1/4	32.0	40,42 € / Stk
103174	G 2	50.0	90,51 € / Stk
103173	G 1 1/2	40.0	59,41 € / Stk
103170	G 3/4	20.0	17,94 € / Stk
103169	G 1/2	15.0	13,16 € / Stk
103168	G 3/8	10.0	12,35 € / Stk
103175	G 2 1/2	65.0	174,90 € / Stk
103176	G 3	80.0	247,32 € / Stk

More Pictures

