


Datasheet for: 103761


Manual sliding valve, G 3/8 ET, AF 22, PN max. 10 bar

Manual sliding valve, Operating temperature °C to 70 °C, G 3/8 ET, AF 22, PN max. 10 bar . For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Type number	3214.73
Article number	103761
EAN/barcode	 4047322224277
Your price	18,63 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

B	31.0 mm
L	87.0 mm
Max. operating pressure	10 bar
Max. operating temperature	70 °C
Page No.	HK347
Preis €	18.63
Thread	G 3/8 ET
a/f	22 mm

Variants

Article number	Thread	a/f	Price
103761	G 3/8 ET	22 mm	18,63 € / Stk
103759	G 1/8 ET	14 mm	10,65 € / Stk
103760	G 1/4 ET	17 mm	13,75 € / Stk

Variants

<i>Article number</i>	<i>Thread</i>	<i>a/f</i>	<i>Price</i>
103762	G 1/2 ET	26 mm	20,62 € / Stk
117407	G 1/2 IT	26 mm	20,54 € / Stk
117405	G 1/4 IT	17 mm	11,58 € / Stk
117406	G 3/8 IT	22 mm	15,53 € / Stk
117404	G 1/8 IT	14 mm	9,07 € / Stk

More Pictures

