


Datasheet for: 107868


Jaw coupling, I.D. 13 (1/2"), DN 10, with safety collar, rotating

Jaw coupling with hose connection, I.D. 13 (1/2"), with safety collar, rotating. Malleable cast iron, galv. and yellow passivated. Universal standard coupling for compressed air lines on construction sites or in industry; standard type according to DIN 3489, used worldwide in a very wide range of applications. - Robust couplings made of malleable iron, zinc plated and yellow chromated - Chrome VI-free, with double safety lock - 100% couple test and secure connection

Type number	KT 13 SBD
Article number	107868
EAN/barcode	 4047322259217
Your price	18,63 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Claw distance	42 mm
DN	10.0
For hose I.D.	13 (1/2)
H	63.0 mm
L	96.0 mm
Material	Malleable iron, zinc plated and yellow chromated
Max. operating pressure	10 bar
Max. operating temperature	95 °C
Min. operating temperature	-40 °C
Page No.	HK612
Safety collar	24.0
Sealant	NBR

Variants

<i>Article number</i>	<i>DN</i>	<i>For hose I.D.</i>	<i>Safety collar</i>	<i>H</i>	<i>Price</i>
107868	10.0	13 (1/2)	24.0	63.0 mm	18,63 € / Stk
107870	19.0	25 (1)	39.0	63.0 mm	18,63 € / Stk
107869	15.0	19 (3/4)	34.0	63.0 mm	18,63 € / Stk