


## Datasheet for: 107870


**Jaw coupling, I.D. 25 (1"), DN 19, with safety collar, rotating**

Jaw coupling with hose connection, I.D. 25 (1"), with safety collar, rotating. Malleable cast iron, galv. and yellow passivated. Universal standard coupling for compressed air lines on construction sites or in industry; standard type according to DIN 3489, used worldwide in a very wide range of applications. - Robust couplings made of malleable iron, zinc plated and yellow chromated - Chrome VI-free, with double safety lock - 100% couple test and secure connection

Type number	KT 25 SBD
Article number	107870
EAN/barcode	 4047322259231
Your price	18,63 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Claw distance	42 mm
DN	19.0
For hose I.D.	25 (1)
H	63.0 mm
L	98.0 mm
Material	Malleable iron, zinc plated and yellow chromated
Max. operating pressure	10 bar
Max. operating temperature	95 °C
Min. operating temperature	-40 °C
Page No.	HK612
Safety collar	39.0
Sealant	NBR

**Variants**

<i>Article number</i>	<i>DN</i>	<i>For hose I.D.</i>	<i>Safety collar</i>	<i>H</i>	<i>Price</i>
107870	19.0	25 (1)	39.0	63.0 mm	18,63 € / Stk
107869	15.0	19 (3/4)	34.0	63.0 mm	18,63 € / Stk
107868	10.0	13 (1/2)	24.0	63.0 mm	18,63 € / Stk