


Datasheet for: 113186


Fitting 340, IT/IT, Rp/Rp 2, black malleable cast iron

Fitting 340, conical sealing, IT/IT, Rp/Rp 2, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFV 340-20
Article number	113186
EAN/barcode	 4047322253161
Your price	18,71 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK864
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	Rp/Rp 2

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
113186	Rp/Rp 2	18,71 € / Stk
113180	Rp/Rp 3/8	5,58 € / Stk
113185	Rp/Rp 1 1/2	12,17 € / Stk
113183	Rp/Rp 1	6,60 € / Stk
113182	Rp/Rp 3/4	5,71 € / Stk
113179	Rp/Rp 1/4	6,03 € / Stk
113184	Rp/Rp 1 1/4	9,85 € / Stk
113181	Rp/Rp 1/2	4,48 € / Stk
113188	Rp/Rp 3	57,66 € / Stk
113187	Rp/Rp 2 1/2	40,03 € / Stk