

18. Juni 2020

1/2

Created on:

Page:

Datasheet for: 141667

Swing safety coupling I.D. 7.2, EURO 7.2, Steel, Hose 11x16



Swing safety coupling I.D. 7.2, EURO 7.2, Steel, Hose connection 11x16, Operating pressure max. 25 bar, Temp. -20 °C to 100 °C . Swing safety coupling with free passage. The plug-in nipple is inserted into the coupling body and rotated by an approx. 90° motion to make the connection. As soon as the "red ring" clicks into the intended slot then a secure connection has been made. To release the connection again, the "red ring" must be pulled out and the plug-in nipple is swivelled to the stopper into the starting position. Venting is done during uncoupling through a vent hole on the back side of the coupling. This coupling meets ISO standard DIN EN ISO 4414, EN 983. These safety couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive.

Type number	424.35-SCH
Article number	141667
EAN/barcode	4047322567695
Your price	28,09 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Page No. HK562 Page No. SK SK045	Surement Housing Length Max. temperature range Medium Min. temperature range Operating pres- Sure Steel, QPQ treated 81.0 mm 100 °C Compressed air, gases -20 °C max. 25 bar / max. 16 bar
----------------------------------	---



Page No. TS Plug profile Sealant Sleeve Threaded piece a/f

TS011 EURO 7.2 NBR Die-cast zinc, nickel-plated, red rubber coated Galvanised steel 24 mm

Variants

Artice number	Comection	418607	*	S). S
141667	Hose connection 11x16	81.0 mm	24 mm	28,09 € / Stk
141666	Hose connection 8x12	76.0 mm	22 mm	28,09 € / Stk

More Pictures



Created on: 18. Juni 2020

User: Gast

Page: 2/2