


Datasheet for: 116037



3/2-way valve, Pneumatic, »3A«, monostable, NO, G 1/4

3/2-way valve, Pneumatic, »3A«, monostable, NO, G 1/4,
 Operating pressure 1.5 - 8 bar, Temperature range max. 70
 °C . 3/2-way pilot valves - Pneumatic -

Type number	516.1003
Article number	116037
EAN/barcode	 4047322309363
Your price	28,17 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4
Control air port	G 1/8
Exhaust connection	G 1/4
Flow rate	850 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	3/2 NO
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Operation	Monostable
Page No.	HK463
Page No. AS	AS083
Size	200
Symbol	24
Valve body	Aluminium alloy

Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
116037	G 1/4	G 1/4	850 l/min	200	28,17 € / Stk
116035	G 1/8	G 1/8	500 l/min	100	25,61 € / Stk
116036	G 1/8	G 1/8	750 l/min	200	28,17 € / Stk
116039	G 3/8	G 3/8	1500 l/min	300	34,68 € / Stk
116038	G 1/4	G 1/4	1300 l/min	300	34,68 € / Stk
116034	M5	M5	300 l/min	100	25,61 € / Stk

More Pictures

