

## Datasheet for: 103498


**Ball valve, High pressure design, Lightweight series, M12x1.5**

Ball valve, High pressure design, Lightweight series, Steel, Operating temp. -10 °C to 100 °C, M12x1.5, DN 4, PN max. 500 bar . For liquid and lubricating media. Available versions: - For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1. - For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1. - With female pipe thread acc. to DIN ISO 228-1 (BSP).

Type number	392.01
Article number	103498
EAN/barcode	 4047322081764
Your price	25,52 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	76.0 mm
B	55.0 mm
Ball	Hard-chrome plated steel
Bore inball	Full bore
Control ball seal	POM
DN	4.0
For tube O.D.	6L mm
Housing	Steel
L	67.0 mm
Max. operating pressure	500 bar
Max. operating temperature	100 °C
Min. operating temperature	-10 °C
Page No.	HK298
Selector shaft	Steel
Selector shaft seal	NBR
Thread	M12x1.5

## Variants

Article number	Thread	Max. operating pressure	DN	For tube O.D.	Price
103498	M12x1.5	500 bar	4.0	6L mm	25,52 € / Stk
103499	M14x1.5	500 bar	6.0	8L mm	24,11 € / Stk
103500	M16x1.5	500 bar	8.0	10L mm	26,32 € / Stk
103501	M18x1.5	500 bar	10.0	12L mm	27,73 € / Stk
103502	M22x1.5	500 bar	12.0	15L mm	30,52 € / Stk
103503	M26x1.5	420 bar	16.0	18L mm	49,51 € / Stk
103504	M30x2	420 bar	20.0	22L mm	59,64 € / Stk
103505	M36x2	420 bar	25.0	28L mm	74,31 € / Stk

## More Pictures

