


## Datasheet for: 106820


**Pneumatically releasable check valve »lineonline« for hose Ø 8 mm**

Pneumatically releasable check valve »lineonline«, Hose - hose, for hose Ø 8 mm, Operating pressure max. 10 bar . For stopping and positioning the cylinder. If a signal is present at the pilot port, air can flow to and from the cylinder. If no pilot signal is present, the cylinder exhaust port is shut off by the stop valve. The cylinder is stopped.

Type number	493-08
Article number	106820
EAN/barcode	 4047322390125
Your price	25,52 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	57.3 mm
B	49.7 mm
Body	Technopolymer
Control air port	4 mm
Flow rate at 6.3 bar and $\Delta p$ 1.0 bar	790 NI/min
For pipe Ø	8.0 mm
Internal parts	18.7 mm
Max. operating pressure	Nickel-plated brass, brass, technopolymer, stainless steel
Max. temperature range	10 bar
Min. temperature range	60 °C
Page No.	-20 °C
Pneumatic symbols	HK494
Sealant	On housing
	NBR

## Variants

Article number	For pipe $\varnothing$	Flow rate at 6.3 bar and $\Delta p$ 1.0 bar	Price
106820	8.0 mm	790 NI/min	25,52 € / Stk
106819	6.0 mm	400 NI/min	25,07 € / Stk

## More Pictures

