

Datasheet for: 107010


2/2-way toggle lever valve, both sides, Quick connector, G 1/8

2/2-way toggle lever valve, both sides, Quick connector for hose 5/3, G 1/8, PN max. 8 bar, Temperature °C to 70 °C. Manually operated toggle valves, 2/2 and 3/2-way types. For all applications where compressed air must be switched on or off quickly and easily or a cylinder operated manually. Designed as a banjo-type valve with a hollow bolt and ring piece. Suitable for screwing directly into the equipment or for panel mounting. Compact type of construction, also ideal where space is restricted.

Type number	360.018-5
Article number	107010
EAN/barcode	 4047322181228
Your price	25,52 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

B	55.0 mm
C	25.0 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	5 / 3 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	8 bar
Max. temperature range	70 °C
Page No.	HK504
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/8
Thread for panel mounting	M12x0.75 (max. plate thickness 4 mm)
Toggle	Nickel-plated brass
Version	2/2-way
a/f	14 mm

Variants

Article number	Thread	For hose	a/f	Price
107010	G 1/8	5 / 3 mm	14 mm	25,52 € / Stk
107009	G 1/8	G 1/8 female thread mm	14 mm	25,52 € / Stk
107011	G 1/8	6 / 4 mm	14 mm	25,52 € / Stk
107012	G 1/8	8 / 6 mm	14 mm	25,52 € / Stk
107013	G 1/4	G 1/4 female thread mm	17 mm	28,77 € / Stk
107014	G 1/4	6 / 4 mm	17 mm	28,77 € / Stk
107015	G 1/4	8 / 6 mm	17 mm	28,77 € / Stk
107016	G 1/4	10 / 8 mm	17 mm	28,77 € / Stk

More Pictures

