

Datasheet for: 141634

Swing safety coupling I.D. 6, ISO 6150 C, Steel, Sleeve I.D. 6



Swing safety coupling I.D. 6, ISO 6150 C, Steel, Sleeve I.D. 6, Operating pressure max. 25 bar, Temp. -20 °C to 100 °C . Swing safety coupling with free passage. The plug-in nipple is inserted into the coupling body and rotated by an approx. 90° motion to make the connection. As soon as the "red ring" clicks into the intended slot then a secure connection has been made. To release the connection again, the "red ring" must be pulled out and the plug-in nipple is swivelled to the stopper into the starting position. Venting is done during uncoupling through a vent hole on the back side of the coupling. This coupling meets ISO standard DIN EN ISO 4414, EN 983. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining.

Type number	423.21-SCH
-------------	------------

Article number	141634
----------------	--------

EAN/barcode	 4047322567497
-------------	---

Your price	25,59 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	I.D. 6
DN	6
Flow rate	820 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Steel, QPQ treated
Length	68.0 mm
Max. temperature range	100 °C
Medium	Compressed air, gases
Min. temperature range	-20 °C
Operating pressure	max. 25 bar / max. 16 bar when attaching / detaching
Page No.	HK564
Page No. SK	SK047
Plug profile	acc. ISO 6150 C
Sealant	NBR
Sleeve	Die-cast zinc, nickel-plated, red rubber coated

Threaded piece
a/f

Galvanised steel
20 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>a/f</i>	<i>Price</i>
141634	I.D. 6	20 mm	25,59 € / Stk
141635	I.D. 8	19 mm	25,59 € / Stk
141636	I.D. 10	20 mm	25,59 € / Stk

More Pictures

