

Datasheet for: 141636

Swing safety coupling I.D. 6, ISO 6150 C, Steel, Sleeve I.D. 10


Swing safety coupling I.D. 6, ISO 6150 C, Steel, Sleeve I.D. 10, Operating pressure max. 25 bar, Temp. -20 °C to 100 °C . Swing safety coupling with free passage. The plug-in nipple is inserted into the coupling body and rotated by an approx. 90° motion to make the connection. As soon as the "red ring" clicks into the intended slot then a secure connection has been made. To release the connection again, the "red ring" must be pulled out and the plug-in nipple is swivelled to the stopper into the starting position. Venting is done during uncoupling through a vent hole on the back side of the coupling. This coupling meets ISO standard DIN EN ISO 4414, EN 983. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining.

Type number	423.24-SCH
-------------	------------

Article number	141636
----------------	--------

EAN/barcode	 4047322567510
-------------	---

Your price	25,59 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	I.D. 10
DN	6
Flow rate	820 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Steel, QPQ treated
Length	68.0 mm
Max. temperature range	100 °C
Medium	Compressed air, gases
Min. temperature range	-20 °C
Operating pressure	max. 25 bar / max. 16 bar when attaching / detaching
Page No.	HK564
Page No. SK	SK047
Plug profile	acc. ISO 6150 C
Sealant	NBR
Sleeve	Die-cast zinc, nickel-plated, red rubber coated

Threaded piece
 a/f

 Galvanised steel
 20 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>a/f</i>	<i>Price</i>
141636	I.D. 10	20 mm	25,59 € / Stk
141634	I.D. 6	20 mm	25,59 € / Stk
141635	I.D. 8	19 mm	25,59 € / Stk

More Pictures

