


## Datasheet for: 116041


**3/2-way valve, Pneumatic, »3A«, monostable, NC, G 1/8**

 3/2-way valve, Pneumatic, »3A«, monostable, NC, G 1/8,  
 Operating pressure 1.5 - 8 bar, Temperature range max. 70  
 °C . 3/2-way pilot valves - Pneumatic -

Type number	516.2001
Article number	116041
EAN/barcode	 4047322309400
Your price	25,61 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1/8
Control air port	G 1/8
Exhaust connection	G 1/8
Flow rate	500 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	3/2 NC
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Operation	Monostable
Page No.	HK463
Page No. AS	AS083
Size	100
Symbol	25
Valve body	Aluminium alloy

## Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
116041	G 1/8	G 1/8	500 l/min	100	25,61 € / Stk
116040	M5	M5	300 l/min	100	25,61 € / Stk
116045	G 3/8	G 3/8	1500 l/min	300	34,68 € / Stk
116042	G 1/8	G 1/8	750 l/min	200	28,17 € / Stk
116043	G 1/4	G 1/4	850 l/min	200	28,17 € / Stk
116044	G 1/4	G 1/4	1300 l/min	300	34,68 € / Stk

## More Pictures

