

Datasheet for: 108048



**Kamlok quick-connect socket with IT, D type, Aluminium, G 3**

Kamlok quick-connect socket with interior thread, D type, Aluminium, G 3, for plug Ø 92 mm, Pressure max. 16 bar, Temp. max. 68 °C . Coupling system for quick and easy connection of two hoses or for joining one hose to a machine connection. A male part and a female part are joined together by shifting the handles. There is no need to turn the hose! Kamlok couplings are used for a wide range of applications in industrial plant and mechanical engineering, tank and container construction, the chemical industry, food processing, mining, refuelling systems, defence technology, etc.

Type number	1114.30
Article number	108048
EAN/barcode	 4047322403283
Your price	19,09 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	131.8 mm
C	89.5 mm
For plug Ø	92.0 mm
Max. operating pressure	16 bar
Max. temperature range	68 °C
Page No.	HK621
Sealant	NBR, resistant to oils and benzine
Thread	G 3

## Variants

Article number	Thread	For plug Ø	Price
108048	G 3	92.0 mm	19,09 € / Stk
108047	G 2 1/2	76.0 mm	14,02 € / Stk
108046	G 2	63.0 mm	11,48 € / Stk
108044	G 1 1/4	45.0 mm	9,20 € / Stk
108049	G 4	120.0 mm	25,61 € / Stk
108043	G 1	37.0 mm	6,68 € / Stk
108042	G 3/4	32.0 mm	5,73 € / Stk
108045	G 1 1/2	53.0 mm	9,73 € / Stk

## More Pictures

