


Datasheet for: 102997


Pressure switch standard design, galvanised steel, 1 - 10 bar

Pressure switch standard design, galvanised steel, Ambient temp. -25 °C to 85 °C, G 1/4, Setting range 1 - 10 bar, NO contact . For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Type number	DS 4015
Article number	102997
EAN/barcode	 4047322126182
Your price	19,10 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjustment range max.	10.0 bar
Adjustment range min.	1.0 bar
Applications	Air, hydraulic oil, oil emulsions, water
Electrical connection	Tab connectors 2 x 6.3 x 0.8
Function	NO
Material	Galvanised steel
Max. ambient temperature	85 °C
Min. ambient temperature	-25 °C
Page No.	HK334
Switching frequency	200/min
Switching voltage	42 V
Thread	G 1/4
Type of construction	Spring-loaded diaphragm (NBR)

Variants

Article number	Thread	Adjustment range min.	Adjustment range max.	Function	Price
102997	G 1/4	1.0 bar	10.0 bar	NO	19,10 € / Stk
102993	G 1/8	0.5 bar	2.0 bar	NO	19,10 € / Stk
102994	G 1/8	1.0 bar	10.0 bar	NO	19,10 € / Stk
102995	G 1/8	10.0 bar	70.0 bar	NO	22,71 € / Stk
102996	G 1/4	0.5 bar	2.0 bar	NO	19,10 € / Stk
102998	G 1/4	10.0 bar	70.0 bar	NO	22,71 € / Stk
102999	G 1/8	0.5 bar	2.0 bar	NC	19,10 € / Stk
103000	G 1/8	1.0 bar	10.0 bar	NC	19,10 € / Stk
103001	G 1/8	10.0 bar	70.0 bar	NC	22,71 € / Stk
103002	G 1/4	0.5 bar	2.0 bar	NC	19,10 € / Stk
103003	G 1/4	1.0 bar	10.0 bar	NC	19,10 € / Stk
103004	G 1/4	10.0 bar	70.0 bar	NC	22,71 € / Stk

More Pictures

