

Datasheet for: 115725


Ball valve »valve line«, Hand lever blue, IT/ET, G 1 1/2

Ball valve »valve line« Hand lever blue, Nickel-plated brass, IT/ET, G 1 1/2, DN 37, Operating temp. -20°C to 120°C, PN max 25 bar . Extremely economical standard ball valves made of nickel-plated brass for compressed air, water, non-toxic and non-corrosive gases and liquids.

Type number	335.08-E
Article number	115725
EAN/barcode	 4047322074360
Your price	25,73 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	138.0 mm
B	70.8 mm
Ball	Nickel-plated brass
Ball seal	PTFE
DN	37.0
Hand lever	Steel Q235-A (1.0038) with PVC-coating
Housing	Nickel-plated brass
L	98.0 mm
Max. operating pressure	25 bar
Max. operating temperature	120 °C
Min. operating temperature	-20 °C
Page No.	WEB
Page No. AS	AS052
Standard thread	G thread acc. to DIN EN ISO 288-1
Stem seal	NBR
Thread	G 1 1/2
Thread material	Nickel-plated brass

Variants

Article number	Thread	DN	Price
115725	G 1 1/2	37.0	25,73 € / Stk
115719	G 1/4	8.0	4,43 € / Stk
115720	G 3/8	10.0	4,43 € / Stk
115721	G 1/2	14.5	4,98 € / Stk
115722	G 3/4	19.0	7,25 € / Stk
115723	G 1	24.5	10,95 € / Stk
115724	G 1 1/4	30.5	17,83 € / Stk
115726	G 2	45.0	41,16 € / Stk

More Pictures

