

## Datasheet for: 107708


**Closing nipple locking on both sides, 1.4305, G 1/8 IT, I.D. 4.3**

Closing nipple locking on both sides, Stainless steel 1.4305, G 1/8 IT, I.D. 4.3, Operating pressure max. 250 bar . Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series. Areas of application: machine and plant engineering, manufacturing industry, chemical / pharmaceutical industry, automotive, food technology.

Type number	246.61
Article number	107708
EAN/barcode	 4047322061476
Your price	28,69 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Ball	Stainless steel 1.4401
Connection	G 1/8 IT
DN	4.3
Flow rate (air)	440 l/min
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Stainless steel 1.4305
Length	29.5 mm
Max. ambient temperature	200 °C
Max. medium temperature	200 °C
Max. operating pressure	250 bar
Min. ambient temperature	-15 °C
Min. medium temperature	-15 °C
Operating pressure	Referred to medium temp. of 50 °C, static working pressure
Page No.	HK603
Page No. SK	SK086
Sealant	FKM
Sleeve	Stainless steel 1.4305
Spring	Stainless steel 1.4310
Valve	Stainless steel 1.4305
a/f	14 mm

## Variants

Article number	Connection	Flow rate (air)	DN	Max. operating pressure	a/f	Price
107708	G 1/8 IT	440 l/min	4.3	250 bar	14 mm	28,69 € / Stk
107709	G 1/4 IT	840 l/min	6.3	250 bar	19 mm	29,33 € / Stk
107710	G 3/8 IT	1280 l/min	7.5	250 bar	22 mm	45,01 € / Stk
107711	G 1/2 IT	1950 l/min	11	250 bar	27 mm	72,80 € / Stk
107712	G 3/4 IT	4500 l/min	13	160 bar	36 mm	132,65 € / Stk

## More Pictures

