

Datasheet for: 103316


Rectangular ball valve, nickel-plated brass, ET/ET, R 1/2

Rectangular ball valve, nickel-plated brass, ET/ET, Operating temp. -15 °C to 100 °C/60 °C gas, R 1/2, PN max. 40 bar/ 5 bar gas .

Type number	350.403
Article number	103316
EAN/barcode	 4047322076180
Your price	19,10 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A Applications	47.0 mm Gas, compressed air, water, oil
B	38.0 mm
Ball seal	PTFE
Butterfly handle	Aluminium, painted yellow
C Ø	31.0 mm
DN	15.0
DVGW approval	DIN EN 331:2013-05
E	37.0 mm
F	35.0 mm
Housing	Nickel-plated brass
Internal parts	Nickel-plated brass
Operating pressure	max. 5 bar (MOP 5) gas, max. 40 bar liquids
Operating temperature	-15 °C to 60 °C for gas, -15 °C to 100 °C for liquids
Page No.	HK290
Standard thread	R thread acc. to ISO 7-1
Stem seal	NBR
Thread	R 1/2
Thread material	Brass with a bare metal surface

Variants

Article number	Thread	DN	Price
103316	R 1/2	15.0	19,10 € / Stk
103317	R 3/4	20.0	28,89 € / Stk
103318	R 1	25.0	39,72 € / Stk

More Pictures

