


Datasheet for: 112921


Fitting elbow 95, IT/IT, Rp 2, black malleable cast iron

Fitting elbow 95, flat sealing, IT/IT, Rp 2, Operating temp. -20°C to 200°C, black malleable cast iron, Hot-dip galvanised . Maximum temperature and maximum operating pressure should not occur at the same time! Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines.

Type number	TFV 95-20
Article number	112921
EAN/barcode	 4047322396202
Your price	28,75 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	200 °C
Min. temperature range	-20 °C
Page No.	HK856
Standard	acc. ISO 7-1
thread	Hot dip galvanised
Surface	Rp 2
Thread	

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
112921	Rp 2	28,75 € / Stk
112920	Rp 1 1/2	19,68 € / Stk
112917	Rp 3/4	6,35 € / Stk
112918	Rp 1	7,91 € / Stk
112919	Rp 1 1/4	13,61 € / Stk
112916	Rp 1/2	5,61 € / Stk