


Datasheet for: 112951


Bracket 120, 45°, IT/IT, Rp 3, black malleable cast iron

Bracket 120, 45°, IT/IT, Rp 3, Operating temperature -20°C to 300°C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

| | |
|----------------|--|
| Type number | TFW 120-30 |
| Article number | 112951 |
| EAN/barcode |  4047322392037 |
| Your price | 28,75 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|------------------------|---|
| Material | Black malleable iron B350-10, design symbol A |
| Max. temperature range | 300 °C |
| Min. temperature range | -20 °C |
| Page No. | HK857 |
| Standard thread | acc. ISO 7-1 |
| Surface | Hot dip galvanised |
| Thread | Rp 3 |

Variants

| <i>Article number</i> | <i>Thread</i> | <i>Price</i> |
|-----------------------|---------------|---------------|
| 112951 | Rp 3 | 28,75 € / Stk |
| 112947 | Rp 1 1/4 | 8,62 € / Stk |
| 112949 | Rp 2 | 12,94 € / Stk |
| 112944 | Rp 1/2 | 2,51 € / Stk |
| 112946 | Rp 1 | 4,48 € / Stk |
| 112948 | Rp 1 1/2 | 10,06 € / Stk |
| 112945 | Rp 3/4 | 2,87 € / Stk |
| 112943 | Rp 3/8 | 3,06 € / Stk |
| 112950 | Rp 2 1/2 | 27,30 € / Stk |