

Datasheet for: 107695


Hydraulic coupling lock on both sides, Brass, G 3/8 IT, I.D. 7.5

Hydraulic coupling locking on both sides, Bright brass, G 3/8 IT, I.D. 7.5, Operating pressure max. 200 bar, Temp. -20°C to 100°C. Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series. Areas of application: machine and plant engineering, manufacturing industry, chemical / pharmaceutical industry, automotive, food technology.

Type number	246.03
Article number	107695
EAN/barcode	 4047322061292
Your price	25,87 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	G 3/8 IT
DN	7.5
Flow rate (air)	1280 l/min
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	64.2 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure	200 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	Referred to medium temp. of 50 °C, static working pressure
Page No.	HK602
Page No. SK	SK085
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Brass with a bare metal surface
Spring	Stainless steel
Valve	Brass with a bare metal surface

a/f

22 mm

Variants

Article number	Connection	Flow rate (air)	DN	Max. operating pressure	a/f	Price
107695	G 3/8 IT	1280 l/min	7.5	200 bar	22 mm	25,87 € / Stk
107693	G 1/8 IT	440 l/min	4.3	250 bar	14 mm	16,60 € / Stk
107694	G 1/4 IT	840 l/min	6.3	200 bar	19 mm	19,35 € / Stk
107696	G 1/2 IT	1950 l/min	11	150 bar	27 mm	36,33 € / Stk
107697	G 3/4 IT	4500 l/min	13	100 bar	34 mm	64,01 € / Stk

More Pictures

