


Datasheet for: 103517


Ball valve, High pressure design, G interior thread, Steel, G 1/2

Ball valve, High pressure design, G interior thread, Steel, Operating temperature -10 °C to 100 °C, G 1/2, DN 12, PN max. 500 bar . For liquid and lubricating media. Available versions: - For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1. - For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1. - With female pipe thread acc. to DIN ISO 228-1 (BSP).

| | |
|----------------|--|
| Type number | 392.24 |
| Article number | 103517 |
| EAN/barcode |  4047322081993 |
| Your price | 28,77 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|--------------------------|
| A | 112.0 mm |
| B | 92.0 mm |
| Ball | Hard-chrome plated steel |
| Bore inball | Full bore |
| Control ball seal | POM |
| DN | 12.0 |
| Housing | Steel |
| L | 82.0 mm |
| Max. operating pressure | 500 bar |
| Max. operating temperature | 100 °C |
| Min. operating temperature | -10 °C |
| Page No. | HK298 |
| Selector shaft | Steel |
| Selector shaft seal | NBR |
| Thread | G 1/2 |

Variants

| Article number | Thread | Max. operating pressure | DN | Price |
|----------------|--------|-------------------------|------|----------------|
| 103517 | G 1/2 | 500 bar | 12.0 | 28,77 € / Stk |
| 103514 | G 1/8 | 500 bar | 4.0 | 27,60 € / Stk |
| 103515 | G 1/4 | 500 bar | 6.0 | 22,48 € / Stk |
| 103516 | G 3/8 | 500 bar | 10.0 | 26,32 € / Stk |
| 103518 | G 5/8 | 420 bar | 16.0 | 112,17 € / Stk |
| 103519 | G 3/4 | 420 bar | 20.0 | 50,32 € / Stk |
| 103520 | G 1 | 420 bar | 25.0 | 64,19 € / Stk |

More Pictures

