


Datasheet for: 107031


3/2-way toggle lever valve, Hose side, Push-in connector, G 1/8

3/2-way toggle lever valve, Hose side, Push-in connector hose 4, G 1/8, PN max. 8 bar, Temp. °C to 70 °C, nickel-plated brass. Manually operated toggle valves, 2/2 and 3/2-way types. For all applications where compressed air must be switched on or off quickly and easily or a cylinder operated manually. Designed as a banjo-type valve with a hollow bolt and ring piece. Suitable for screwing directly into the equipment or for panel mounting. Compact type of construction, also ideal where space is restricted.

Type number	3615.018-4
Article number	107031
EAN/barcode	 4047322181464
Your price	28,77 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

B	55.0 mm
C	19.5 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	4 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	8 bar
Max. temperature range	70 °C
Page No.	HK505
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/8
Thread for panel mounting	M12x0.75 (max. plate thickness 4 mm)
Toggle	Nickel-plated brass
Version	3/2-way
a/f	14 mm

Variants

Article number	Thread	For hose	a/f	Price
107031	G 1/8	4 mm	14 mm	28,77 € / Stk
107032	G 1/8	6 mm	14 mm	28,77 € / Stk
107033	G 1/8	8 mm	14 mm	28,77 € / Stk
107034	G 1/4	6 mm	17 mm	31,81 € / Stk
107035	G 1/4	8 mm	17 mm	31,81 € / Stk
107036	G 1/4	10 mm	17 mm	31,81 € / Stk

More Pictures

