


Datasheet for: 100512



Filter »multifix«, Polycarbonate container, 5 µm, Size 1, G 1/4

Filter »multifix« with polycarbonate container, 5 µm, Size 1, G 1/4, Input pressure max. 16 bar, Medium / ambient temp. max. 60 °C . Centrifugal separators with a sintered filter element.

Type number	F 11 K-HA
Article number	100512
EAN/barcode	 4047322344173
Your price	28,96 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	47.8 mm
B	152.1 mm
Bowl	Polycarbonate container
C	27.0 mm
Condensate drain	Semi-automatic
D	125.1 mm
DN	6.0
Filter rating	5.0 µm
Flow rate	2100 l/min
Flow rate measurement	At P ₁ = 6 bar and pressure drop Δ _p = 1 bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Page No.	HK084
Series	multifix
Size	1
Thread	G 1/4

Variants

Article number	Thread	Housing	Filter rating	Flow rate	DN	Size	Price
100512	G 1/4	Die-cast zinc	5.0 μm	2100 l/min	6.0	1	28,96 € / Stk
100514	G 1/2	Die-cast zinc	5.0 μm	4000 l/min	15.0	3	52,04 € / Stk
100516	G 1	Aluminium	40.0 μm	8000 l/min	25.0	5	156,89 € / Stk
100513	G 3/8	Die-cast zinc	5.0 μm	2100 l/min	10.0	1	28,96 € / Stk
100515	G 3/4	Die-cast zinc	5.0 μm	4000 l/min	20.0	3	52,04 € / Stk

More Pictures

