

Characteristics

Type	F 11	F 12		
Port	G 1/4	G 3/8		
Type of construction		Centrifugal filter Sintered filter element		
	Special versi	Special versions on request		
Input pressure p ₁		Max. 16 bar with plastic bowl Max. 20 bar with metal bowl		
Input pressure p ₁				
with fully-automatic drain	Max. 10 bar	Max. 10 bar		
	Min. 1.5 bar			
Mounting position	Vertical, drain plu	ug at bottom		
Mounting type	Bracket and two	Bracket and two through holes		
Medium temperature	Max. 60 °C (other	Max. 60 °C (other temperature		
Ambient temperature		Max. 60 °C ranges on request)		
Filter rating	5 μm	. ,		
Bowl capacity	Max. 25 cm ³ con	Max. 25 cm³ condensate		
Condensate drain	Semi-automatic	Semi-automatic		
	Fully-automatic of	on request		
Weight [g]	275			

Materials

Part	Material
Head piece (body)	Z 410
O-ring 30x2	NBR
Filter element 5 µm	Polyethylene (sintered)
Air deflector	POM
Baffle	PA
Condensate bowl	Polycarbonate



FXX X

Port		
11	G 1/4	
12	G 3/8	
Options		
K-HA	Plastic bowl	
M-SR	Metal bowl with sight glass	
S	Bowl guard	

Please use the suffix **A**« to order fully-automatic drain

Order example: F 11 K-HA

Description


- Block design
- Simple block mounting of several devices with conical clamps and half threads
- Joiner sets (KP 11) are required for block mounting
- Flow direction indicated by arrows
- Entry in direction of arrow
- Filter rating acc. to ISO 4003, glass bead test
- Bowl guard can be retrofitted without tools

12/2014 Data subject to change 1.1

Compressed air conditioning



Dimensions [mm]




Flow rates

Output pressure $p_2 = [bar]$		6
Nominal flow ($\Delta p = 1 \text{ bar}$)	QN m³/h l/min	126 2100
	1/111111	2100

Main spare parts

Part	Part No.
Filter element 5 µm	611.6.905

Flow characteristic



Accessories

Designation	Order No.
Mounting bracket with 2 screws, cmpl.	ZW 11
Joiner set(s) for block mounting with other devices	KP 11
Joiner set for narrow diverter block	KP 11 Z
Bowl guard	SK 11
Metal bowl with sight glass	MS 11 FS
Metal bowl with sight glass and fully-automatic drain	MS 11 FS-A
Polycarbonate bowl with semi-automatic drain valve	KS 11 F-HA
Polycarbonate bowl with fully-automatic drain valve	KS 11 F-A
Filter element 5 µm	611.6.905
Automatic drain valve	655.6.900

© Riegler 1-2