


Datasheet for: 107369


Quick-connect coupling I.D. 7.6 »stream line«, gal. steel / brass

Quick-connect coupling I.D. 7.6, »stream line«, galvanised steel / brass, for hose 13.5x9.5, Operating pressure max. 16 bar . High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates. Specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. The stream line type has an integrated hose stem.

Type number	244.93-1
Article number	107369
EAN/barcode	 4047322390286
Your price	26,24 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

DN	7.6
Flow rate	2100 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
For hose	13.5x9.5 mm
Housing	Steel
Length	68.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure	16 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	WEB
Sealant	NBR
Sleeve	Hardened and nickel-plated steel
Spring	Stainless steel
a/f 1	21.0 mm
a/f 2	20.0 mm

Variants

Article number	For hose	Length	a/f 1	a/f 2	Price
107369	13.5x9.5 mm	68.0 mm	21.0 mm	20.0 mm	26,24 € / Stk
107370	16x11 mm	68.0 mm	24.0 mm	24.0 mm	31,61 € / Stk
107368	12x8 mm	68.0 mm	19.0 mm	20.0 mm	26,92 € / Stk
107367	10x6.5 mm	64.0 mm	16.0 mm	20.0 mm	26,65 € / Stk

More Pictures

