

Acc. to DIN 4817 (Sheet 1) - DVGW approved.

Material	Brass with a bare metal surface or chrome-plated brass
Operating pressure	Max. 16 bar for valves with a cutting ring fitting Max. 4 bar for valves with a pipe thread
Operating temperature	-20 °C to 60 °C
Applications	Fuel oil, liquefied gas (in gas phase), compressed air
Port	G thread acc. to DIN EN ISO 228-1

Quick-stop shut-off valves, brass

Art. No.	Ident No.	Connection	DN
230.30 B	103743	G 1/4 female	7
230.40 B	103744	G 3/8 female	8
230.50 B	103745	G 1/2 female	12
230.15 B	103746	6 mm pipe connection	4
230.25 B	103747	8 mm pipe connection	6
230.35 B	103748	10 mm pipe connection	7
230.45 B	103749	12 mm pipe connection	10
230.55 B	103750	15 mm pipe connection	12



230.40 B



230.25 B

Quick-stop shut-off valves, chrome-plated brass

Art. No.	Ident No.	Connection	DN
230.30 V	103751	G 1/4 female	7
230.40 V	103752	G 3/8 female	8
230.50 V	103753	G 1/2 female	12
230.15 V	103754	6 mm pipe connection	4
230.25 V	103755	8 mm pipe connection	6
230.35 V	103756	10 mm pipe connection	7
230.45 V	103757	12 mm pipe connection	10
230.55 V	103758	15 mm pipe connection	12



230.40 V



230.25 V