


Datasheet for: 103751


Quick connect blocking valve, Brass chrome plated, G 1/4 IT

Quick connect - blocking valve, Brass chrome plated, DIN 4817 DVGW accepted, G 1/4 IT, DN 7, PN max. 16 bar .

Type number	230.30 V
Article number	103751
EAN/barcode	 4047322054522
Your price	26,29 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Applications	Fuel oil, liquefied gas (in gas phase), compressed air
Connection	G 1/4 male
DN	7.0
DVGW approval	DIN 4817-1:1981-04
Material	Chrome-plated brass
Max. operating pressure	16 bar
Max. operating temperature	60 °C
Min. operating temperature	-20 °C
Page No.	HK347
Standard thread	G thread acc. to DIN EN ISO 228-1

Variants

<i>Article number</i>	<i>Connection</i>	<i>Max. operating pressure</i>	<i>DN</i>	<i>Price</i>
103751	G 1/4 male	16 bar	7.0	26,29 € / Stk
103752	G 3/8 male	16 bar	8.0	27,16 € / Stk
103753	G 1/2 male	16 bar	12.0	53,77 € / Stk
103754	6 mm pipe connection	4 bar	4.0	29,26 € / Stk
103755	8 mm pipe connection	4 bar	6.0	25,53 € / Stk
103756	10 mm pipe connection	4 bar	7.0	27,80 € / Stk
103757	12 mm pipe connection	4 bar	10.0	32,66 € / Stk
103758	15 mm pipe connection	4 bar	12.0	53,77 € / Stk