


## Datasheet for: 103508


**Ball valve, High pressure design, Heavy-duty series, M20x1.5**

Ball valve, High pressure design, Heavy-duty series, Steel, Operating temp. -10 °C to 100 °C, M20x1.5, DN 8, PN max. 500 bar . For liquid and lubricating media. Available versions:  
 - For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1. - For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1. - With female pipe thread acc. to DIN ISO 228-1 (BSP).

Type number	392.13
Article number	103508
EAN/barcode	 4047322081887
Your price	26,32 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	100.0 mm
B	68.0 mm
Ball	Hard-chrome plated steel
Bore inball	Full bore
Control ball seal	POM
DN	8.0
For tube O.D.	12S mm
Housing	Steel
L	77.0 mm
Max. operating pressure	500 bar
Max. operating temperature	100 °C
Min. operating temperature	-10 °C
Page No.	HK298
Selector shaft	Steel
Selector shaft seal	NBR
Thread	M20x1.5

## Variants

Article number	Thread	Max. operating pressure	DN	For tube O.D.	Price
103508	M20x1.5	500 bar	8.0	12S mm	26,32 € / Stk
103506	M16x1.5	500 bar	4.0	8S mm	24,11 € / Stk
103507	M18x1.5	500 bar	6.0	10S mm	25,52 € / Stk
103509	M22x1.5	500 bar	10.0	14S mm	27,73 € / Stk
103510	M24x1.5	500 bar	12.0	16S mm	30,52 € / Stk
103511	M30x2	420 bar	16.0	20S mm	49,51 € / Stk
103512	M36x2	420 bar	20.0	25S mm	57,55 € / Stk
103513	M42x2	420 bar	25.0	30S mm	74,31 € / Stk

## More Pictures

