

## Datasheet for: 103255


**Safety ball valve not lockable, Venting hole, Rp 1/2**

Safety ball valve, not lockable, with venting hole, nickel-plated brass, Operating temp. max. 60°C, Rp 1/2, DN 15, PN max. 12 bar . Brass safety ball valves. Specially designed for pneumatic applications. The ball valve shuts off the supply side and relieves the application into the atmosphere.

Type number	350.503
Article number	103255
EAN/barcode	 4047322076401
Your price	19,45 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	100.0 mm
B	64.0 mm
Ball	Nickel-plated brass
DN	15.0
Hand lever	Die-cast aluminium, black
Housing	Nickel-plated brass
L	69.0 mm
Max. operating pressure	12 bar
Max. operating temperature	60 °C
Page No.	HK281
Page No. SF	SF044
Sealant	PTFE
Standard thread	Rp thread acc. to ISO 7-1
Stem	Nickel-plated brass
Stuffing box	Nickel-plated brass
Thread	Rp 1/2
Thread material	Brass with a bare metal surface

## Variants

Article number	Thread	DN	Price
103255	Rp 1/2	15.0	19,45 € / Stk
103253	Rp 1/4	8.0	18,29 € / Stk
103254	Rp 3/8	10.0	18,29 € / Stk
103256	Rp 3/4	20.0	30,87 € / Stk
103257	Rp 1	25.0	38,56 € / Stk
103258	Rp 1 1/4	32.0	62,79 € / Stk
103259	Rp 1 1/2	40.0	86,89 € / Stk
103260	Rp 2	50.0	133,37 € / Stk

## More Pictures

