


Datasheet for: 107877


Safety jaw coupling with exterior thread, G 3/4, DN 17

Safety jaw coupling with exterior thread, G 3/4, DN 17, Malleable cast iron, Operating pressure max. 16 bar, Temp. -40°C to 95°C. Universal standard coupling in safety design according to DIN 3238 for absolutely secure compressed air lines on construction sites or in industry. Easy to couple, secured against accidental opening: just screw the ring tight after coupling! - Robust couplings with malleable iron head, steel stem with special profile, zinc plated and yellow chromated - Chrome VI-free, with double safety lock - Large bore for increased flow rate

| | |
|----------------|--|
| Type number | KA 34 S |
| Article number | 107877 |
| EAN/barcode |  4047322260060 |
| Your price | 19,45 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|----------------|
| Claw distance | 42 mm |
| DN | 17.0 |
| H | 63.0 mm |
| L | 70.2 mm |
| Material | Malleable iron |
| Max. operating pressure | 16 bar |
| Max. operating temperature | 95 °C |
| Min. operating temperature | -40 °C |
| Page No. | HK613 |
| Page No. SF | SF078 |
| Sealant | NBR |
| Thread | G 3/4 |
| a/f | 24 mm |

Variants

| <i>Article number</i> | <i>DN</i> | <i>Thread</i> | <i>a/f</i> | <i>Price</i> |
|-----------------------|-----------|---------------|------------|---------------|
| 107877 | 17.0 | G 3/4 | 24 mm | 19,45 € / Stk |
| 107875 | 10.0 | G 3/8 | 24 mm | 19,45 € / Stk |
| 107878 | 17.0 | R 1 | 36 mm | 23,19 € / Stk |
| 107876 | 13.0 | G 1/2 | 24 mm | 19,45 € / Stk |