

Datasheet for: 106968


Throttle valve, Both sides throttling (»B«) G 1/2 IT, G 1/2

Throttle valve, Both sides throttling (»B«) Threaded connection G 1/2 IT, G 1/2, PN max. 10 bar, Temperature °C to 70 °C . For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. Compact type of construction, also ideal where space is restricted.

Type number	359.012-1/2
Article number	106968
EAN/barcode	 4047322393867
Your price	29,05 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjusting screw	Nickel-plated brass
B	61.0 mm
C	32.0 mm
Captive seals	Polyamide (glass fibre-reinforced)
Connection	G 1/2 female thread
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK502
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/2
a/f	26 mm

Variants

Article number	Thread	Connection	a/f	Price
106968	G 1/2	G 1/2 female thread	26 mm	29,05 € / Stk
106964	M5	M5 female thread	8 mm	9,72 € / Stk
106965	G 1/8	G 1/8 female thread	14 mm	9,72 € / Stk
106966	G 1/4	G 1/4 female thread	17 mm	10,60 € / Stk
106967	G 3/8	G 3/8 female thread	20 mm	18,90 € / Stk

More Pictures

