


Datasheet for: 112913


Bracket 94, 90°, ET/ET, R 1 1/4, black malleable cast iron

Bracket 94, 90°, ET/ET, R 1 1/4, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFW 94-114
Article number	112913
EAN/barcode	 4047322347990
Your price	19,65 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK856
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	R 1 1/4

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
112913	R 1 1/4	19,65 € / Stk
112912	R 1	6,14 € / Stk
112915	R 2	16,84 € / Stk
112914	R 1 1/2	16,35 € / Stk
112911	R 3/4	4,02 € / Stk
112909	R 3/8	3,06 € / Stk
112910	R 1/2	3,55 € / Stk