


## Datasheet for: 101501


**Inline pressure regulator, 2 x IT, G 1/4, AF 17, pre-set 7 bar**

Inline pressure regulator, 2 x IT, without secondary venting, G 1/4, AF 17, Working pressure (pre-set) 7 bar, PN max. 18 bar . This single-acting diaphragm regulator can be installed in any pneumatic system. Since the pressure is preset in the factory and cannot be altered, the product is also tamper-proof. We recommend mounting the regulator directly on the tool to make sure the correct pressure is applied. In this case, the tool is never stressed by the higher pressure of the supply system and is protected against pressure fluctuations in hoses, pipes, etc. Energy efficiency and economic efficiency can be achieved by using an inline pressure regulator.

Type number	637.22
Article number	101501
EAN/barcode	 4047322203876
Your price	26,50 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	34.0 mm
B	52.0 mm
Flow rate	800 l/min
Flow rate measurement	At P 1 = 12 bar and pressure drop $\Delta p = 0.5$ bar
Housing	Zinc
Internal parts	Brass, NBR, stainless steel
Max. operating pressure	18 bar
Max. temperature range	60 °C
Page No.	HK175
Page No. SF	SF032
Series	inline
Thread	G 1/4
Working pressure (preset)	7.0 bar
a/f	17 mm

## Variants

Article number	Working pressure (preset)	Price
101501	7.0 bar	26,50 € / Stk
101494	1.0 bar	26,50 € / Stk
101495	2.0 bar	26,50 € / Stk
101496	3.0 bar	26,50 € / Stk
101497	4.0 bar	26,50 € / Stk
101498	5.0 bar	26,50 € / Stk
101499	6.0 bar	26,50 € / Stk
101500	6.5 bar	26,50 € / Stk

## More Pictures

